Jandel Engineering Limited



Jandel Portable Measurement System

Jandel Engineering Limited offers the HM21 Test Unit in combination with the Hand Applied Probe as a solution for making measurements where portability is a key factor. The system can be used for measuring a wide variety of samples from thin layers and wafers up to large ingots. The probe head can have loads of up to 200g per needle and the Hand Applied Probe has a large downward force of around 1.2Kg and so is not suitable for fragile unsupported samples.

Max. sample size	Any reasonable size sample can be measured as long as the Hand Applied Probe can be placed appropriately	
Max. sample thickness	Any thickness of sample can be measured as long as the Hand Applied Probe can be placed appropriately	
Toggle Switch	Prevents current flow when probe is not in contact with the sample	
Manual Placement	Probe is designed to be placed and left while measurement is made to avoid fluctuation associated with hand held measurement	
Simple set up	Single wire connects the Hand Applied Probe and HM21	

Туре	Tip R	Force	Spacing
A	40u	100g	1mm
В	100u	100g	1mm
С	200и	100g	1mm
D	500u	70g	1mm
Е	40u	200g	1.591mm
F	40u	100g	0.635mm
G	100и	100g	0.635mm
Н	200и	100g	0.635mm

Type A-D and F-H are user adjustable in the range 60g-150g and supplied at value shown



If you require any further information on the Jandel Portable Measurement system please contact us using the details below